

Do More  
with Less

**FILM** PELID 22  
EN



**PELid 22** is the new mono-oriented co-extruded high barrier, PE or PP sealing layer film, the thinnest currently available on the market for packaging products in a protective atmosphere, such as red meat, white meat, sausage, fish, cheese, fresh pasta, ready meals, fruits and vegetables. Glossy, anti-condensation, resistant, highly workable: this is **PELid 22**.

<b>Main characteristics</b>	
<b>Reduced thickness</b>	Only 25 microns of thickness. Environmental impact reduced to a minimum.
<b>Barrier property</b>	PELid 22 is suitable for the packaging of fresh products in a protective atmosphere, thanks to the presence of the EVOH layer.
<b>Two sealing types</b>	PELid 22 is available in a version with PE sealing and with PP sealing, ideal for packaging rigid and polystyrene trays. Both versions allow for a tight seal and excellent sealing of trays.
<b>Ideal for packaging fresh and very fresh products</b>	Red meat, white meat, fish, cheese, baked goods, fresh pasta, ready meals, fruits and vegetables.
<b>Excellent shine, transparency, anti-condensation properties</b>	Guarantee of optimal presentation of the packaged product throughout its shelf-life.
<b>Mechanical strength</b>	The manufacturing process makes the product particularly resistant to handling and perforation.
<b>Manageability</b>	The production characteristics of PELid 22 allow for machine performance to be maximised and film performance to be optimised.
<b>The ideal combination is with automatic tray-sealing machines produced by Gruppo Fabbri</b>	Ideal use is with Gruppo Fabbri tray-sealing machines from the XPEED and TopLid families present in industrial lines of food industry processors. Use is also possible with a wide range of packaging machines available on the market.
<b>Wide range of solutions</b>	The material is also available with 45 and 60 microns of thickness, without EVOH and with widths ranging from 150 to 600 mm.

**25** Thickness 25 µm.

**76** Inner reel core 76 mm.

**210** Min width 210 mm.

**550** Max width 550 mm.

**1200** Minimum length of 1200 m, ideal for retail.

**1600** Max length of 1600 m, ideal for industrial use.

The data refers to standard production, our sales staff are always at your disposal for non-standard requests.

Gruppo Fabbri Vignola guarantees quick, efficient and widespread technical assistance, thanks to a team of qualified and multi-lingual professionals, always at the disposal of customers.

**DISCLAIMER** The content and information provided in this brochure are intended for general marketing purposes, therefore no subject (person or company) must consider them exact or complete. Gruppo Fabbri Vignola, its company organisations, managers, officials, employees, agents and consultants will not be held liable (including liability resulting from error or negligence, without any limitation) for any direct or indirect loss, damage, cost or obligation which could have been suffered resulting from the use or reliance on that contained or omitted in this brochure. Gruppo Fabbri Vignola reserves the right to modify the specifics of its products without any prior notice. For further technical or economical information, please contact the Gruppo Fabbri Vignola Sales Department.

